

Technical Data Sheet

2024-02-27

* Not a stock item. Please contact your local Plus Pack sales rep.

Product group: READY2COOK®
Description: ROUND.Ø111.214ML.GOLD
Item number: 0021409800



Product Specifications

| | |
|----------------|---------------------|
| Shape | ROUND |
| Compartment | 1-COMPARTMENT |
| Closing option | SEALABLE/RETORT |
| Application | FREEZER / MICROWAVE |

Temperature

| | |
|-------------------|-------|
| Inside temp. Min | -40°C |
| Inside temp. Max | 130°C |
| Outside temp. Min | -40°C |
| Outside temp. Max | 200°C |

| | |
|----------------------|--------|
| Volume | 214 ml |
| Capacity/compartment | 214 ml |
| Top out length | 111 mm |
| Top out width | 0 mm |
| Top in length | 99 mm |
| Top in width | 0 mm |
| Base length | 89 mm |
| Base width | 0 mm |
| Height | 31 mm |

Packaging Specifications

| | |
|----------------------------|-----------------------------|
| Quantity/bag | 2520 (+/- 2%) ² |
| Quantity/crt. | 2520 (+/- 2%) ² |
| Quantity/pal. | 40320 (+/- 2%) ² |
| EAN-code bag | |
| EAN-code crt. | 5701022192814 |
| EAN-code pal. | 5701022192821 |
| Weight/1 pc. | 5.543 g (+/- 10%) |
| Weight/1000 pcs. | 5.5 kg |
| Weight/crt. | 14.8 kg |
| Weight/pal. (excl. pallet) | 236.3 kg |
| Volume/crt. | 0.109 m3 |
| Size/crt. | 59 * 40 * 47 cm |
| Size/pal. (height) | 201 cm |
| Cartons/pal. | 16 |
| Cartons/layer | 4 |
| Layers/pal. | 4 |

Material Specifications

| | |
|------------------|---------------------------------|
| Material | ALU COATED ¹ |
| Mono-material | YES |
| Color (in/out) | COLORLESS / GOLD |
| Recycled content | 0% * |
| Foil description | LAMINATE / LACQUER ³ |
| Inside lacquer | PP laminate |

¹ This product is made of a valuable material. Please recycle where possible.

The aluminium foil contains a food approved lubricate, the amount is depending on the shape and complexity of the container.

² The number of packagings may vary, but the number is equalized by the total order.

³ Be aware that containers with outside and/or inside lacquer can have limitations on the specified temperature. Lacquer is specified to app. 200°C, but time, food and other conditions may affect heat resistance, therefore it must be tested at the customer. For more information on specific food stuffs, see relevant DOC.

* The recycled content in % is the secondary production aluminium part. This is a calculated average based on raw material supplier data for the last 2 calendar years. It can be subject to changes based on changes from our supplier.

Matching Item

0029002006

